

PU



1.5mm

2.0mm



2m x 27.5m = 55m²

2m x 20m = 40m²



2360g/m²

3200g/m²



GENERAL PERFORMANCE

EN 649

ASTM F1913



REACTION TO FIRE

UIC 564-2: 1991 Conforms

95/28/EC Conforms

ISO 3795 0mm/mn

BS 6853: 1999 Class 1b †

EN 13501-1 Class Bfl-S1 { EN ISO 9239-1 ≥8kw/m²
EN ISO 11925-2 Pass

ASTM E662 <450

ASTM E648 Class 1 †2.0mm



SLIP RESISTANCE

EN 13893 Class DS

AS/NZS 4586 R9



ABRASION RESISTANCE

EN 649 Group M



LOAD

ASTM F970 750 psi (modified)



MARITIME USAGE

American Bureau of Shipping†

US Coast Guard†

Marine Equipment Directive†

96/98/EC as amended 2002/75/EC

SOLAS 74

China Classification Society Approved†

ClassNK Approved† †2.0mm



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Voyager.



POLYFLOR LTD. - TRANSPORT FLOORING DIVISION

PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK

TEL: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 2515

E-MAIL: TRANSPORT@POLYFLOR.COM

WWW.VOYAGER.POLYFLOR.COM

James Halstead™
FLOORING



2006